


1.1.3 VSR-SA.

Circular VAV terminals integral sound attenuator



AIRFLOW MEASUREMENT AND CONTROL

Application

Single duct VAV (Variable-Air-Volume) terminals are commonly used to maintain a constant space temperature by varying the conditioned air volume to the space. If the space temperature raises above the set point, the primary air damper modulates open to supply more (cold) primary air into the space so that the required space temperature is maintained. As the space temperature drops below set point, the VAV terminal modulates to a pre-set minimum airflow, which is usually determined by the minimum level of ventilation required in the space. Should the space cooling loads drop even further at the minimum airflow setting, a reheat coil (hot water or electric) can be energized to provide further heating.

Single duct VAV terminals can also be used to maintain a constant (positive or negative) room pressure and to control the carbon dioxide (CO₂) level in the room.



Type VSR-SAS-BE1 with integral sound attenuator


Design features

Casing

- Ridged galvanised steel construction (1,0mm or 20 gauge).
- Spigots comply with DIN 24145 or DIN 24146.
- Oval shaped damper blade, sandwich construction with synthetic rubber seals. Leakage rate 0.25% of V_{nom} @ 750Pa (3"WG) static pressure drop.
- Air leakage flow complies with Class II, VDI 3803 or DIN 24194, Part 2
- Damper shaft aluminium, ø12 mm
- Bearings Polyamide (PA6.6)
- Thermal / acoustical insulation 25kg/m³ (1,5lb/cuFt) fire resistant to BS-476 Class "O".
- Operating temperature +5 to 50°C (controls)
- Storage temperature 0 to +70°C, max R.H. 95%
- Other construction available upon request.

Air flow sensor


- The unique shape, patent pending, creates a linear amplified signal (at least 2.5x P_{dyn}) with a very low pressure drop and noise level.
- Multi point averaging according to the "Log-Tchebycheff" method
- 2% (FS) accuracy with 3xDeq straight duct approach
- 5% (FS) accuracy with 1xDeq straight duct approach
- Stable measuring signal from 0,7 m/s air velocity



Detail FloXact-X® multipoint, averaging air flow sensor

Kv Values FloXact-X®

	units	100	125	160	200	250	315	355	400	450	500
Kv Value	l/s/Pa	5,23	8,89	15,6	25,5	41,3	67,5	86,8	111,3	142,2	176,8
	m ³ /h/Pa	18,8	32,0	56,2	91,9	148,8	243,0	312,3	400,7	511,8	636,5
V _{nom} @ 150Pa	l/s	64	109	191	313	506	827	1.063	1.363	1.741	2.165
	m ³ /h	231	392	688	1.125	1.822	2.976	3.825	4.908	6.268	7.795
V _{nom} @ 250Pa (1"WC)	l/s	83	141	247	404	653	1.067	1.372	1.760	2.248	2.795
	m ³ /h	298	506	888	1.453	2.352	3.842	4.938	6.336	8.093	10.064



Accessories / Optional

The units are supplied as standard with controls on the right side (seen in the air direction).

- Standard Controls:
BE1 Belimo LMV-D3-MP
GR1 Grüner 327VM-024-05
BEM Belimo LMV-D3-MOD
GRM Grüner 327VM-024-05-MB
The above controllers are factory mounted, calibrated and, if desired, provided with a location label.
- If desired, Air-Concepts can install free issue controls. We have suitable mounting consoles for all common control manufacturers.
- Transformer 230/24V AC (20 or 30VA)
- Hot water duct heater 1-, 2-, or 3-row.
- Duct cooler 3-row.
- Electric duct heater.

Dimensions and weight (without controls)


		100	125	160	200	250	315	355	400	450	500
$\varnothing d$	mm	$\varnothing 98$	$\varnothing 123$	$\varnothing 158$	$\varnothing 198$	$\varnothing 248$	$\varnothing 313$	$\varnothing 353$	$\varnothing 398$	$\varnothing 448$	$\varnothing 498$
$\varnothing d2$	mm	$\varnothing 200$	$\varnothing 225$	$\varnothing 260$	$\varnothing 300$	$\varnothing 350$	$\varnothing 415$	$\varnothing 455$	$\varnothing 500$	$\varnothing 550$	$\varnothing 600$
L	mm	500	500	500	500	500	500	500	500	550	600
VSR-SW	Kg	1,1	1,4	1,9	2,5	3,3	4,5	5,3	6,2	6,7	8,9
VSR-DW	Kg	3,0	3,6	4,4	5,4	6,8	8,6	9,8	11,3	12,2	15,0
VSR-SAx	Kg	7,3	7,9	9,4	11,2	13,5	16,6	18,6	20,9	x	x

Sound data dB(A) and NR

1. The discharge sound pressure levels $L_p(A)$, are determined with a room absorption of 7dB/oct and the following assumption for downstream ductwork, diffuser(s) and end reflection:

125	250	500	1k	2k	4k	Hz
-3	-5	-10	-15	-15	-12	dB

2. The discharge sound pressure levels $L_p(A)$ also include a correction for air volume :



3. The Radiated sound pressure levels $L_p(A)$ are determined with a room absorption of 7dB/oct and the following assumption ceiling attenuation:

125	250	500	1k	2k	4k	Hz
-1	-3	-5	-7	-7	-10	dB

4. Sound data is measured in a reverberation room at an independent sound laboratory, according to ISO-3741 and ISO-5135 standards.
5. L_w in dB/Oct are sound power levels (re $10^{-12}W$) per octave band in dB for discharge sound and radiated sound. Values less than 17 dB are indicated by "-".
6. n/a Not applicable, static pressure < unit resistance
7. min ΔP_s . Unit resistance with fully opened damper blade

Sound data NC

1. The sound pressure levels $L_p(A)$, are determined with the following attenuation factors according to the guidelines in ARI-885-98

2. The discharge sound pressure levels include:
>Environmental effect

125	250	500	1k	2k	4k	Hz
-3	-2	-1	-1	-1	-1	dB

- >Duct lining, 5 feet, 1" lining (1.5m, 25mm thick)

125	250	500	1k	2k	4k	Hz
-1	-3	-8	-21	-20	-12	dB

- >End Reflection

125	250	500	1k	2k	4k	Hz
-11	-6	-2	0	0	0	dB

- >Acoustical flexible duct 5 ft 8" (1.5m ϕ 200mm)

125	250	500	1k	2k	4k	Hz
-6	-10	-17	-19	-19	-12	dB

- >Room effect. 3000 cu ft, 10 ft from source.

125	250	500	1k	2k	4k	Hz
-9	-10	-11	-12	-13	-14	dB

- >Discharge sound total reduction in dB:

125	250	500	1k	2k	4k	Hz
-30	-31	-39	-53	-53	-39	dB

3. The Radiated sound pressure levels include:

- >Environmental effect

125	250	500	1k	2k	4k	Hz
-3	-2	-1	-1	-1	-1	dB

- >Ceiling effect. Mineral fibre 5/8" 20 lb/cu ft

125	250	500	1k	2k	4k	Hz
-9	-10	-12	-14	-15	-15	dB

- >Room effect. 3000 cubic ft, 10 ft from source.>

125	250	500	1k	2k	4k	Hz
-9	-10	-11	-12	-13	-14	dB

- >Radiated sound total reduction in dB:


125	250	500	1k	2k	4k	Hz
-21	-22	-24	-27	-29	-30	dB

4. Sound data is measured in a reverberation room at an independent sound laboratory, according to ISO-3741 and ISO-5135 standards.
5. L_w in dB/Oct are sound power levels (re $10^{-12}W$) per octave band in dB for discharge sound and radiated sound. Values less than 17 dB are indicated by "-".
6. n/a Not applicable, static pressure < unit resistance
7. min ΔP_s . Unit resistance with fully opened damper blade

Model	Air Vel.	Air Volume				Min. P _{st}	Discharge sound (Air borne sound)									Radiated sound (Break out sound)										
							Lw (dB/oct) re 10 ⁻¹² W						Quick Sel. L _p			Lw (dB/oct) re 10 ⁻¹² W						Quick Sel. L _p				
							125 Hz	250 Hz	500 Hz	1k Hz	2k Hz	4k Hz	dB (A)	NR	NC	125 Hz	250 Hz	500 Hz	1k Hz	2k Hz	4k Hz	dB (A)	NR	NC		
mm	m/s	m ³ /h	l/s	CFM	Pa																					
100	0,7	19	5	11	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	3,0	80	22	47	4	28	-	-	-	-	-	-	-	-	-	25	21	20	-	-	-	-	-	-	-	-
	6,0	160	44	94	16	36	28	23	18	-	-	-	-	-	-	32	26	25	22	-	-	-	-	-	-	-
	9,0	239	67	141	36	43	38	34	30	25	19	22	-	-	-	36	30	28	25	-	-	-	-	-	-	-
	12,0	319	89	188	64	50	46	42	38	33	28	29	24	-	-	39	32	30	27	-	18	-	-	-	-	-
125	0,8	32	9	19	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	3,0	126	35	74	4	33	20	-	-	-	-	-	-	-	-	28	23	22	18	-	-	-	-	-	-	-
	6,0	253	70	149	15	42	31	25	20	-	-	-	-	-	-	36	28	27	23	-	-	-	-	-	-	-
	9,0	379	105	223	33	48	40	36	32	27	21	25	19	-	-	42	32	30	26	-	18	-	-	-	-	-
	12,0	505	140	297	59	52	48	44	40	35	30	31	26	-	-	41	34	32	28	18	19	22	-	-	-	-
160	0,8	56	16	33	0	23	17	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	3,0	209	58	123	3	36	28	18	-	-	-	-	-	-	-	24	25	23	19	-	-	-	-	-	-	-
	6,0	418	116	246	13	44	35	29	22	17	-	-	-	-	-	32	30	28	24	-	18	-	-	-	-	-
	9,0	627	174	369	30	50	43	39	34	29	24	26	20	-	-	36	34	31	28	18	20	20	-	-	-	-
	12,0	836	232	492	53	55	50	46	42	37	32	31	26	-	-	39	36	33	30	19	21	21	-	-	-	-
200	0,8	92	26	54	0	27	25	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	3,0	329	91	194	3	42	35	26	-	-	19	-	-	-	-	26	25	22	18	-	18	-	-	-	-	-
	6,0	658	183	387	12	49	42	33	25	20	22	24	-	-	-	33	31	28	23	18	21	-	-	-	-	-
	9,0	988	274	581	28	54	47	41	36	31	27	28	22	-	-	37	34	31	26	20	23	-	-	-	-	-
	12,0	1317	366	775	50	59	53	49	44	39	35	32	27	-	-	40	36	33	29	22	24	19	-	-	-	-
250	0,9	149	41	88	0	31	27	20	-	-	17	-	-	-	-	-	17	-	-	-	-	-	-	-	-	-
	3,0	517	144	304	3	44	38	30	-	18	24	-	-	-	-	29	28	25	23	17	21	-	-	-	-	-
	6,0	1035	287	609	13	49	44	37	27	24	27	23	-	-	-	33	33	30	28	21	24	-	-	-	-	-
	9,0	1552	431	913	29	55	49	44	38	33	31	27	22	-	-	38	37	33	31	23	26	-	-	-	-	-
	12,0	2070	575	1218	51	60	55	51	46	41	37	32	27	-	-	43	39	35	34	24	27	20	-	-	-	-
315	0,9	243	67	143	0	33	32	25	-	18	23	-	-	-	-	18	18	17	-	-	-	-	-	-	-	-
	3,0	826	229	486	3	46	42	34	18	24	29	22	-	-	-	31	28	26	24	20	22	-	-	-	-	-
	6,0	1651	459	971	12	54	48	40	29	29	33	26	21	-	-	38	34	32	30	24	26	-	-	-	-	-
	9,0	2477	688	1457	26	59	53	47	40	36	36	29	24	-	-	43	37	35	33	26	28	-	-	-	-	-
	12,0	3303	917	1943	47	63	58	53	48	43	40	33	28	-	-	46	39	37	35	27	29	19	-	-	-	-
355	0,9	312	87	184	0	35	34	27	-	23	28	-	-	-	-	19	19	18	-	-	20	-	-	-	-	-
	3,0	1051	292	618	3	48	44	37	22	29	34	23	19	-	-	32	29	28	25	22	26	-	-	-	-	-
	6,0	2102	584	1236	11	55	50	43	32	33	38	27	22	-	-	39	35	33	31	26	30	-	-	-	-	-
	9,0	3153	876	1855	25	57	55	48	41	38	40	28	25	-	-	39	38	36	34	28	32	-	-	-	-	-
	12,0	4204	1168	2473	44	62	59	54	49	45	43	32	29	-	-	43	41	38	36	29	33	19	-	-	-	-
400	0,9	401	111	236	0	32	37	30	-	25	29	-	-	-	-	-	21	20	-	-	20	-	-	-	-	-
	3,0	1337	371	786	3	48	47	39	26	31	35	24	20	-	-	32	31	29	26	23	26	-	-	-	-	-
	6,0	2674	743	1573	10	56	52	45	34	35	39	27	23	-	-	40	36	34	32	27	30	-	-	-	-	-
	9,0	4011	1114	2359	24	61	57	50	43	40	41	30	26	-	-	44	40	37	35	29	32	-	-	-	-	-
	12,0	5348	1485	3146	42	65	61	56	51	46	44	33	29	-	-	47	42	39	37	30	33	20	-	-	-	-

Model	Air Vel.	Air Volume			Min. P _{st}	Discharge sound (Air borne sound)									Radiated sound (Break out sound)											
						Lw (dB/oct) re 10 ⁻¹² W						Quick Sel. L _p			Lw (dB/oct) re 10 ⁻¹² W						Quick Sel. L _p					
						125 Hz	250 Hz	500 Hz	1k Hz	2k Hz	4k Hz	dB (A)	NR	NC	125 Hz	250 Hz	500 Hz	1k Hz	2k Hz	4k Hz	dB (A)	NR	NC			
mm	m/s	m ³ /h	l/s	CFM	Pa																					
100	0,7	19	5	11	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	3,0	80	22	47	4	32	21	-	-	-	-	-	-	-	29	26	26	22	-	18	-	-	-	-	-	-
	6,0	160	44	94	16	40	30	23	18	-	-	-	-	36	32	31	27	19	22	20	-	-	-	-	-	-
	9,0	239	67	141	36	45	39	34	30	25	19	23	-	40	35	34	30	21	24	23	-	-	-	-	-	-
	12,0	319	89	188	64	51	46	42	38	33	28	29	24	-	43	37	36	32	23	25	26	20	-	-	-	-
125	0,8	32	9	19	0	21	-	-	-	-	-	-	-	-	-	17	17	-	-	-	-	-	-	-	-	-
	3,0	126	35	74	4	37	25	-	-	-	-	-	-	-	32	28	28	23	17	20	-	-	-	-	-	-
	6,0	253	70	149	15	46	33	26	20	-	-	-	-	40	34	33	28	21	23	22	-	-	-	-	-	-
	9,0	379	105	223	33	51	41	36	32	27	21	27	22	-	46	37	36	32	23	25	26	19	-	-	-	-
	12,0	505	140	297	59	53	48	44	40	35	30	31	26	-	45	39	38	34	24	27	27	22	-	-	-	-
160	0,8	56	16	33	0	27	23	-	-	-	-	-	-	-	-	20	19	-	-	-	-	-	-	-	-	-
	3,0	209	58	123	3	40	33	24	-	-	20	-	-	-	28	30	29	25	19	22	-	-	-	-	-	-
	6,0	418	116	246	13	48	40	31	23	18	23	24	-	36	36	34	30	22	25	23	-	-	-	-	-	-
	9,0	627	174	369	30	53	45	39	34	29	27	28	23	-	40	39	37	33	24	27	25	20	-	-	-	-
	12,0	836	232	492	53	57	51	47	42	37	33	32	27	-	43	42	40	35	26	28	26	21	-	-	-	-
200	0,8	92	26	54	0	31	30	22	-	-	20	-	-	-	-	20	19	-	-	19	-	-	-	-	-	-
	3,0	329	91	194	3	46	41	32	-	17	26	-	-	-	30	31	29	23	21	25	-	-	-	-	-	-
	6,0	658	183	387	12	53	47	38	26	23	29	28	23	-	37	36	34	29	25	28	22	-	-	-	-	-
	9,0	988	274	581	28	58	51	43	36	31	32	31	26	-	41	40	37	32	27	30	23	-	-	-	-	-
	12,0	1317	366	775	50	61	55	49	44	39	36	34	29	-	44	42	39	34	28	32	24	19	-	-	-	-
250	0,9	149	41	88	0	35	33	27	-	18	25	-	-	-	20	23	22	19	17	22	-	-	-	-	-	-
	3,0	517	144	304	3	48	43	36	20	25	31	26	21	-	33	33	31	28	24	28	21	-	-	-	-	-
	6,0	1035	287	609	13	52	49	42	29	29	34	28	24	-	37	39	36	34	27	31	23	-	-	-	-	-
	9,0	1552	431	913	29	58	53	46	38	35	37	31	26	-	43	42	39	37	30	33	24	-	-	-	-	-
	12,0	2070	575	1218	51	63	57	52	46	42	40	34	30	-	47	45	42	39	31	35	25	19	-	-	-	-
315	0,9	243	67	143	0	37	38	31	-	24	31	-	-	-	22	24	23	20	20	24	-	-	-	-	-	-
	3,0	826	229	486	3	50	48	41	24	31	37	27	23	-	35	34	33	30	27	30	20	-	-	-	-	-
	6,0	1651	459	971	12	58	54	46	32	35	40	31	27	-	43	39	38	35	30	33	23	-	-	-	-	-
	9,0	2477	688	1457	26	62	57	50	41	39	43	33	29	-	47	43	41	38	33	35	24	-	-	-	-	-
	12,0	3303	917	1943	47	66	61	55	48	44	45	35	31	-	50	45	43	41	34	37	25	19	-	-	-	-
355	0,9	312	87	184	0	39	40	34	18	29	36	23	22	-	23	25	25	21	22	28	-	-	-	-	-	-
	3,0	1051	292	618	3	52	50	43	28	36	42	29	25	-	36	35	34	31	29	34	21	19	-	-	-	-
	6,0	2102	584	1236	11	59	56	48	35	39	45	32	28	-	43	41	39	36	32	37	23	19	-	-	-	-
	9,0	3153	876	1855	25	60	60	52	42	42	47	33	30	-	43	44	42	40	34	39	24	20	-	-	-	-
	12,0	4204	1168	2473	44	65	63	56	50	47	49	35	32	-	47	47	44	42	36	41	25	20	-	-	-	-
400	0,9	401	111	236	0	37	42	36	22	32	37	24	23	-	21	26	26	23	24	28	-	-	-	-	-	-
	3,0	1337	371	786	3	53	52	45	31	38	43	30	26	-	36	36	35	32	30	34	21	-	-	-	-	-
	6,0	2674	743	1573	10	60	58	51	37	42	47	32	29	-	44	42	40	38	34	38	23	19	-	-	-	-
	9,0	4011	1114	2359	24	65	62	54	44	44	49	34	31	-	48	45	44	41	36	40	24	19	-	-	-	-
	12,0	5348	1485	3146	42	68	65	58	51	48	50	37	33	21	51	48	46	43	37	41	25	19	-	-	-	-

Model	Air Vel.	Air Volume			Min. P _{st}	Discharge sound (Air borne sound)									Radiated sound (Break out sound)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
						Lw (dB/oct) re 10 ⁻¹² W						Quick Sel. L _p			Lw (dB/oct) re 10 ⁻¹² W						Quick Sel. L _p																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								
						125 Hz	250 Hz	500 Hz	1k Hz	2k Hz	4k Hz	dB (A)	NR	NC	125 Hz	250 Hz	500 Hz	1k Hz	2k Hz	4k Hz	dB (A)	NR	NC																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
mm	m/s	m³/h	l/s	CFM	Pa																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																								



Type:

- VSR - VAV terminal met round in- and outlet. Supply and return application.

Construction:

- SA - Single wall construction

Model:

- Ø - 100, 125, 160, 200, 250, 315, 355, 400, 450 or 500

Controls:

- BE0 - Belimo LMV-D3-FX (5Nm w/o NFC)
- BE1 - Belimo LMV-D3-MP (5Nm)
- BE2 - Belimo NMV-D3-MP (10Nm)
- BE3 - Belimo VRU-D3-BAC + LM24A-VST (5Nm, 150sec/90°)
- BE4 - Belimo VRU-D3-BAC + LMQ24A-VST (5Nm, 2,5sec/90°)
- BE5 - Belimo VRU-M1-BAC + LMQ24A-VST (5Nm, 2,5sec/90°)
- BEM - Belimo LMV-D3-MOD
- GR1 - Grüner 327VM-024-05
- GRM - Grüner 327VM-024-05-MB

Specify as:

Example:

Supply and install, VAV terminal, double wall constructing, from galvanized sheet steel, duct sleeve connections suitable for DIN 24 145 or DIN 24 146. Casing leakage rate to class II, VDI 3803/ DIN 24 194. The VAV units should have a low leakage, sandwich construction damper blade with SBR gasket and an aluminium damper shaft with self lubricating Nylon bearings and averaging airflow sensor type FloXact®.

For:

Air volume	 m ³ /h
Unit size	 mm
Max. pressure loss	 Pa
Max. discharge SPL	 dB(A)
Max. radiated SPL	 dB(A)
Controller	Belimo LMV-D3-MP (factory fitted and calibrated)
Manufacturer	AIR-CONCEPTS BV
Type	VSR-SA.-250-BE1-xxx-

Air-Concepts locations

Head Office:
AIR-CONCEPTS BV
De Compagnie 22E
1620 AG Hoorn
The Netherlands
+31 229 262 300
info@air-concepts.nl
www.air-concepts.nl

Factory:
AIR-CONCEPTS d.o.o.
Obrtniška ulica 25
8010 Trebnje
Slovenia
+386 31 34 22 79
j.pekolj@air-concepts.nl



Sales UK:
BARCOL-AIR UK Ltd
128, City Road
London, EC1V 2NX
United Kingdom
+44 1225 310309
info@barcol-air.co.uk
www.barcol-air.co.uk

Sales Middle East:
AIR-CONCEPTS FZ-LLC
Al Hamra Industrial Zone-FZ
Ras Al Khaimah
United Arab Emirates
info@air-concepts.nl
www.air-concepts.nl